

Tub liniar fluorescent daylight T5 HE - 14 W

- Indice mare de redarea a culorii
- temperatura culorii ridicata



Cod		FTHE6514
Cod ILCOS		FD-14/65/1A-E-G5-16/550
Putere (nom.)	P	14 W
Putere (specif.)	P	13.7 W
Curent	I	170 mA
Fisa de date IEC		6520
Flux luminous	Φ	950 lm
Flux luminous 35 °C	Φ	1040 lm
Eficacitate luminoasa	η	69.3 lm/W
Eficacitate luminoasa 35 °C	η	75.9 lm/W
Temperatura ambientala	T(Φmax)	35 °C
Lungime	l	550 mm
Index de redare a culorii	Ra/CRI	93
Clasa de redare a culorii		1A
Temperatura culorii	Tcp/CCT	6500 K
Codul de culoare al luminii		965
Indice circadian	Ac	95
Continutul maxim de mercur		3 mg
EEl of balast		A1, A2+BAT, A3
Durata de viata asteptata		24000 h
Clasa energetica		B
Conexiune		G5
Diametrul tubului		T5
Tara de origine		DE
EAN13 (1)		8595229200192
EAN13 (25)		8595229203346

NASLI®

NATURAL SPECTRUM LIGHTING

