

Tub liniar fluorescent daylight T5 HO - 49 W

- Indice mare de redarea a culorii
- temperatura culorii ridicata



| | | |
|-----------------------------|----------------|--------------------------|
| Cod | | FTHO6549 |
| Cod ILCOS | | FD-49/65/1A-E-G5-16/1450 |
| Putere (nom.) | P | 49 W |
| Putere (specif.) | P | 49.3 W |
| Curent | I | 260 mA |
| Fisa de date IEC | | 6750 |
| Flux luminous | Φ | 3900 lm |
| Flux luminous 35 °C | Φ | 4250 lm |
| Eficacitate luminoasa | η | 79.1 lm/W |
| Eficacitate luminoasa 35 °C | η | 86.2 lm/W |
| Temperatura ambientala | T(Φ max) | 35 °C |
| Lungime | l | 1450 mm |
| Index de redare a culorii | Ra/CRI | 93 |
| Clasa de redare a culorii | | 1A |
| Temperatura culorii | Tcp/CCT | 6500 K |
| Codul de culoare al luminii | | 965 |
| Indice circadian | Ac | 95 |
| Continutul maxim de mercur | | 3 mg |
| EEl of balast | | A1, A2+BAT, A3 |
| Durata de viata asteptata | | 24000 h |
| Clasa energetica | | B |
| Conexiune | | G5 |
| Diametrul tubului | | T5 |
| Tara de origine | | DE |
| EAN13 (1) | | 8595229201472 |
| EAN13 (25) | | 8595229201489 |

