

## Tub liniar fluorescent daylight T5 HO – 80 W

- Indice mare de redarea a culorii
- temperatura culorii ridicata



Cod		FTHO6580
Cod ILCOS		FD-80/65/1A-E-G5-16/1450
Putere (nom.)	P	80 W
Putere (specif.)	P	80 W
Curent	I	530 mA
Fisa de date IEC		6850
Flux luminous	$\Phi$	5700 lm
Flux luminous 35 °C	$\Phi$	6200 lm
Eficacitate luminoasa	$\eta$	71.3 lm/W
Eficacitate luminoasa 35 °C	$\eta$	77.5 lm/W
Temperatura ambientala	T( $\Phi$ max)	35 °C
Lungime	l	1450 mm
Index de redare a culorii	Ra/CRI	93
Clasa de redare a culorii		1A
Temperatura culorii	Tcp/CCT	6500 K
Codul de culoare al luminii		965
Indice circadian	Ac	95
Continutul maxim de mercur		3 mg
EEl of balast		A1, A2+BAT, A3
Durata de viata asteptata		24000 h
Clasa energetica		B
Conexiune		G5
Diametrul tubului		T5
Tara de origine		DE
EAN13 (1)		8595229200383
EAN13 (25)		8595229200420

